

borg &
overström



Beautifully
refreshing.

b5

borg&
overström

A design like no other

The B5 range straddles the line between high-end functionality and ultra-modern design. The unique streamlined design of this range will bring sophistication to any environment.

Reasons to choose

- Optimum height for interaction
- Fully open, illuminated dispense area
- Shrouded faucet for hygienic protection
- Compact, alarmed drainage system
- Built-in leak detector

borgandoverstrom.com



Beautifully
refreshing.

b5

Water system



Direct Chill

Configuration



Floorstanding

Water options



Chilled



Ambient



11-25



25+

Number of users



Hot



Sparkling

Available colours



Silver



Beautifully
refreshing.

Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



Ultra-violet sterilising system
For added hygiene confidence, appliances can be fitted with Viovand™ – an ultra-violet sterilisation process that reduces water-born bacteria.



World-class filtration
For the ultimate drinking experience, Borg & Overström appliances can be pre-fitted with a 3M filter to reduce sediment, chlorine, odours and scale.



Laboratory certified 99.999% bacteria-free
Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



Biofilm, limescale and impact resistant epoxy resin panel finish
Providing an increased level of hygiene and longevity, Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

Beautifully refreshing.

B5 Models	Silver	Power requirements	Dimensions	WxDxH
		Hertz 50/Volts 220-240	Floorstanding	520x415x1310mm
		Max power consumption	Dispense height	250mm
Direct Chill, Floorstanding		Chilled & Ambient 100W		
Chilled, Ambient	101520	Chilled, Ambient & Sparkling 140W		
Chilled, Ambient, Sparkling	101530	Chilled, Ambient & Hot 900W		
Chilled, Ambient, Hot	101540	Chilled, Hot & Sparkling 940W		
Chilled, Hot, Sparkling	101550			
		Chilled temperature		
		Min 2°C/Max 11°C		
		Hot temperature		
		Max 92°C		
		Throughput litres per hour		
		Chilled 35/Hot 6		



Beautifully
refreshing.

Additions for B5



Printed paper cups
Environmentally-friendly disposable cups designed to fit Borg & Overström cup dispensers perfectly.



Deep-sparkle CO² refills
Can be disposed via standard steel recycling or general waste. Requires CO² regulator with gauge.



Sanitisation kit
Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



Install kit with 3M filter
Install appliances simply and effectively in a wide range of applications. Complete with a 3M filter.



Ultra-violet filter kit
Complete Viovandt™ filter kit to assist in water purification and removal of unwanted micro-organisms.



Wall bracket kit
For added security, use the wall bracket set to anchor your watercooler back to the wall. Simple to fit and unobtrusive.



CO² housing
A complete cover to protect and improve aesthetic appeal when using a large refillable CO² cylinder. Ideal for public areas.

Beautifully
refreshing.

borg&
overström

Book a visit to the Borg & Overström Academy
for a personal demonstration of the B5

Talk to an adviser
+44 (0) 1362 695 006
sales@borgandoverstrom.com